

DN 15 – 100
(½ – 4")

DN 125 – 200
(5 – 8")



Non-Return Valve RK 44 For flanges PN 6 / 10/16

Description

Wafer-type non-return (check) valve for sandwiching between flanges. Valve with spring for installation in any position. Without spring only for vertical lines with upward flow. Self-centering ring or self-centering valve body ensures accurate installation. Application for liquids, gases and vapours (observe classification according to PED).

Pressure/Temperature Rating for valves with metal-to-metal seat

Nominal sizes DN	[mm] [in]	15 – 100 ½ – 4			125 – 200 5 – 8		
Nominal pressure	PN	16 ¹⁾					
Max. service pressure	[bar] [psig]	16 230	14 200	13 185	16 230	14 200	13 185
Related temperature	[°C] [°F]	120 248	200 392	250 482	120 248	200 392	250 482
Minimum temperature		–200 °C (–328 °F) ¹⁾			–10 °C (14 °F) ¹⁾		

¹⁾ Minimum temperature at nominal pressure rating.

Soft seats

EPDM (ethylene propylene): –40 to +150°C (–58 to +302°F) for water, condensate and steam.
FPM (fluoro rubber): –25 to +200°C (–13 to +392°F) for oils, gases and air.

But also note valve pressure/temperature rating in the above table.

Tightness with soft seats of EPDM and FPM in accordance with DIN 3230, part 3, leakage rates BN 1, BO 1. Permissible leakage rates with metal-to-metal seat in accordance with DIN 3230, part 3, leakage rates BN 2, BO 3.

Chemical resistance see GESTRA data base "Chemical Resistance".

Connections of wafer-type valves ²⁾

DIN	Standard valves for fitting between flanges to	
	BS	ASME
DIN EN 1092, PN 6/10/16	BS 10 tables D, E, F	B 16.1 class 125 FF B 16.5 class 150 RF ³⁾

²⁾ DN 15–100 mm (½–4") with universal centering ring.

³⁾ ASME class 150 RF only suitable for DN 125–200 mm (5–8").

Dimensions

DN	[mm] [Inch]	15 ½	20 ¾	25 1	32 1¼	40 1½	50 2	65 2½	80 3	100 4	125 5	150 6	200 8
Dimensions	L ⁴⁾	16	19	22	28	31,5	40	46	50	60	90	106	140
	Ø D	42	49	58	74	84	97	117	132	152	184	209	264
Weight	[kg]	0.1	0.2	0.25	0.5	0.7	1.1	1.4	2	3.2	7.7	11	22

⁴⁾ Overall length according to DIN EN 558-1, table 11, series 49 (≅ DIN 3202, part 3, series K4).

Materials

DN 15 – 100 (½ – 4")	DIN reference		ASTM equivalent
Body, seat and guide ribs	CuSn 10 – Cu	CC480K-GS	B 584 C90 500
Valve disc, spring retainer	X6CrNiMoTi17-12-2	1.4571	A182F316
Spring			A313 Type 316
Centring ring	X10CrNi18-8	1.4310	A313 Type 302
DN 125 – 200 (5 – 8")			
Body	EN-GJL-250	EN-JL 1040	A126 Class A
Seat, valve cone and spindle	CuSn10 – Cu	CC480K-GS	B 584 C90 500
Guide support			
Spindle guide			
Spring	X6CrNiMoTi17-12-2	1.4571	A313 Type 316

Non-Return Valve RK 44 For flanges PN 6/10/16

Opening pressures

Differential pressures at zero volume flow.

DN	Opening pressures [mbar]			
	Direction of flow			
	without springs	with springs		
	↑	↑	→	↓
15	2.5	10	7.5	5
20	2.5	10	7.5	5
25	2.5	10	7.5	5
32	3.5	12	8.5	5
40	4.0	13	9	5
50	4.5	14	9.5	5
65	5.0	15	10	5
80	5.5	16	10.5	5
100	6.5	18	11.5	5
125	12.5	35	22.5	10
150	14.0	38	24.0	10
200	13.5	37	23.5	10

On request at extra charge, special springs for opening pressures: between 5 and 1000 mbar for DN 15–50 mm, between 5 and 700 mbar for DN 65 and 80 mm, between 5 and 500 mbar for DN 100–200 mm.

Enquiry Specification

GESTRA DISCO non-return valve RK 44, PN 6/10/16.
Wafer design with extremely short overall length to DIN EN 558-1, table 11, series 49.
Suitable for fitting between flanges to DIN, BS or ASME.
Indications on pressure, nominal size (DN), body material.
Metal-to-metal seat or soft seat (EPDM or FPM).

Order Specifications

Type RK 44, DN...
Metal-to-metal or soft seat (EPDM or FPM).
Fluid, flowrate, pressure and temperature.
Type of pipe flanges.

Note

The valves should not be used on compressors or where pulsating flow exists.
For these applications please consult us.



These products comply with the requirements of the EC Pressure Equipment Directive (PED) 97/23/EC. Classified for application in fluids of group 2 (non-hazardous substances). DN 65–200 with CE marking. DN 15–50 are excluded from the scope of this Directive and **not entitled** to bear the CE marking.

Supply in accordance with our general terms of business.

GESTRA AG

P.O.Box 10 54 60, D-28054 Bremen
Münchener Str. 77, D-28215 Bremen
Telefon 0049 (0) 421 / 35 03 - 0, Telefax 0049 (0) 421 / 35 03-393
E-Mail gestra.ag@flowserve.com, Internet www.gestra.de

Pressure Drop Chart

The curves given in the chart are valid for water at 20 °C. To read the pressure drop for other fluids the equivalent water volume flowrate \dot{V}_w must be calculated.


The pressure drops indicated in the chart are valid for valves fitted with a standard spring for installation in horizontal lines and for valves without spring for vertical flow lines with the flow from bottom to top.

$$\dot{V}_w = \dot{V} \cdot \sqrt{\frac{\rho}{1000}}$$

\dot{V}_w = Equivalent water volume flow in [l/s] etc.

ρ = Density of fluid (operating condition) in [kg/m³] etc.

\dot{V} = Volume of fluid (operating condition) in [l/s] etc.



- Required minimum volume flowrate \dot{V}_w for equipment fitted with standard spring for installation in horizontal lines.
- Required minimum volume flowrate \dot{V}_w for equipment without spring for installation in vertical lines with the flow from bottom to top.



GESTRA

Distributor : Energy Technology Co., Ltd.

Tel.: +66 2 721 3860 - Fax.: +66 2 721 3869 - E-mail: sales@energytechnology.co.th - http:// www.energytechnology.co.th